

SENSITHERM S.r.l.

Fire Resisting Control & Power cables
Micatape, XLPE insulated, LSOH outer sheath



Type MICA/XLPE/LSOH 0,6/1 KV 3G1,5 mm²

Conductor

Plain annealed copper conductor according to IEC60228 cl. 5.

Insulation

Mica tape over the conductor

Cross-linked Polyethylene compound according to IEC 60502-1

Thicknes of insulation > 0,8 mm

Identification cores :

Black, Blue, Yellow/Green

Layin ap

Core stranded with at least 10 twists/meter

Outer sheath

LSOH compound M1 type according to EN 50290-2-27, black

Thicknes of jacket => 1,8 mm

Overall diameter 12,7±0,3 mm

Marking

Sensitherm - MT/XLPE/LSOH 0,6/1 KV 3G1,5 IEC 60331-21

Performance

Resistance to fire - Circuit Integrity acc. IEC 60331-21

Reaction to fire - Flame propagation a) Test of single cable acc. IEC 60332.1

b) Test on bunched cables acc. IEC 60332-3-24

Minimum bending radius

6 times overall diameter

Technical data & Electrical properties

Temperature range -30 + 90°C

Temperature laying - 5 + 50°C

Conductor resistance : < 13,3 Ohm/Km

Insulation resistance : > 5.000 Mohm x Km

Test voltage - Core/core : 4.000 V

Operating voltage max 1 KV