

DATA SHEET Type : FR2 ((4X(2X1,5HR)) + 6X1,5) OHRAE 0,6/1Kv

Four pairs 1,5sqmm :

- Conductor : Flexible plain copper conductor according to IEC60228 cl. 5
size 1,50sqmm (28x0,25).
Res. 13,3ohm/Km
- Insulation : Polyvinylchloride PVC flame retardant color :
Blue-Black numbered
Conductor diameter over insulation 2,8mm
- Individual screen : Over the pair will be wrapped with Mylar tape and shielded with Aluminum/Mylar
tape 100% coverage and 25% overlap with metal side in contact with a tinned copper
drain wire 7x0,30 size 0,5sqmm
- Outer sheath : Polyvinylchloride PVC flame retardant
Thickness 1,0 mm
External diameter 7,8mm
External color Black

Six conductors 1,5sqmm :

- Conductor : Flexible plain copper conductor according to IEC60228 cl. 5
size 1,5sqmm (28x0,25).
Res. 13,3ohm/Km
- Insulation : Polyvinylchloride PVC flame retardant color :
Black numbered
Conductor diameter over insulation 2,8mm

Total assembly : Four pairs and six cores will be twisted together

Overall screen : Over the rope will be wrapped with Mylar tape and shielded with Aluminum/Mylar
tape 100% coverage and 25% overlap with metal side in contact with a tinned copper
drain wire 7x0,30 size 0,5sqmm

- Bedding :** Polyvinylchloride PVC flame retardant
Thickness 1,0 mm
- Armor :** SWB galvanized steel wire braid coverage 80%
- Outer sheath :** Polyethylene extruded compound PE
Thickness 2 mm
External diameter 23,4mm +/- 10%
External color Black
- Marking :** On the outer sheath will be written with ink-jet printer
“ year SENSITHERM description cable “
- Performance :** Test voltage core to core 3,5 Kv
Working temperature -15 +70°C
Minimum bending radius 290mm
Aprox. Weight 1080Kg/Km