

**POWER CABLE  
Cu, HEPR insulated, CWB, LSZH outer sheath  
IEC60332.3, IEC60754, IEC61034**

---

<b>Type</b>	<b>F-Cu/HEPR/CWB/LSZH 0,6/1Kv FG7OH2M1 0,6/1Kv</b>	<b>4G 1,5sqmm</b>
<b>Conductor :</b>	Flexible red copper conductor according to IEC60228 cl.5 size Diam. 1,55 mm	1,5sqmm ( 28x0,25 )
<b>Insulation :</b>	Cross-linked HEPR extruded compound Thickness : 0,7 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
<b>Laying up :</b>	Twisted to core, color Y/G - Brown - Black - Grey ( or to be agreed )	

**Overall screen**

<b>Bedding :</b>	PET tape Thickness : mm
<b>Screen :</b>	CWB red copper wire braid Thickness : 0,2 mm
<b>Outer sheath :</b>	M1, Low Smoke Zero Halogen emission extruded compound Color : Black ( or to be agreed ) Thickness : 1,6 mm Overall diameter : 11,4 mm Total weight : 230 Kg/Km

**Marking :**

On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.

<b>Performance :</b>	- Conductor resistance 13,3 ohm/Km (+ 5% for multipair ) - Test voltage core to core 4 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and halogen free as per IEC60754-2, CEI20-37/2 - Low smoke density emission IEC61034-1/2 - Minimum bending radius 12 V. D. - Hydrocarbon resistant
----------------------	---

**Weight and diameter are theoretical + / - 10%**