

**POWER CABLE
Cu, HEPR insulated, LSZH bedding, CWB, LSZH outer sheath
IEC60332.3, IEC60502**

Type	F-Cu/HEPR/LSZH/CWB/LSZH 0,6/1Kv FG7OH2M1 0,6/1Kv	4X 4sqmm
Conductor :	Flexible red copper conductor according to IEC60228 cl.5 size Diam. 2,5 mm	4sqmm (56x0,30)
Insulation :	Cross-linked HEPR extruded compound Thickness : 0,7 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
Laying up :	Twisted to core, color Blue - Brown - Black - Grey	

Overall screen

Bedding :	M1, Low Smoke Zero Halogen emission extruded compound Thickness : 1,0 mm
Screen :	CWB red copper wire braid Thickness : 0,2 mm
Outer sheath :	M1, Low Smoke Zero Halogen emission extruded compound Color : Black (or to be agreed) Thickness : 1,6 mm Overall diameter : 17 mm Total weight : 570 Kg/Km

Marking :

On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.

Performance :	- Conductor resistance 4,95 ohm/Km (+ 5% for multipair) - Test voltage core to core 4 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and halogen free as per IEC60754-2, CEI20-37/2 - Low smoke density emission IEC61034-1/2 - Minimum bending radius 12 V. D. - Hydrocarbon resistant
----------------------	---

Weight and diameter are theoretical + / - 10%