

INSTRUMENTATION CABLE
Cu, EPR insulated, individual Al screen, Copper braid overall screen, PVC outer sheath
IEC60332.3

Type	F-Cu/EPR/IS/CWB/PVC 0,6/1Kv FG7XHOH2R 0,6/1Kv	9X2X 0,5sqmm
Conductor :	Flexible plain copper conductor according to IEC60228 cl.5 size 0,5sqmm (16x0,20) Diam. 0,9 mm	
Insulation :	Cross-linked HEPR extruded compound Thickness : 0,7 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
Laying up :	Twisted to core, color Blue - Black numbered (or to be agreed)	
Pair/Triad screen	Applied over the single pair/triad will be wrapped with polyester tape and shielded with Aluminum / Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 size 0,5sqmm, over the screen will be placed a further Mylar tape.	
Bedding :	Mylar tape Thickness : mm	
Screen :	CWB plain copper wire braid Thickness : 0,2 mm	
Outer sheath :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Grey (or to be agreed) Thickness : 2,0 mm Overall diameter : 20 mm Total weight : 620 Kg/Km	
Marking :	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
Performance :	- Conductor resistance 39 ohm/Km (+ 5% for multipair) - Test voltage core to core 4 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and fume as per IEC60754-1, CEI20-37 - HCL emission <= 22% - Minimum bending radius 12 V. D. - Hydrocarbon resistant - Inductance <= 0,90 mH/Km - Capacitance <= 0,250 microF/Km	

Weight and diameter are theoretical + / - 10%