

**INSTRUMENTATION CABLE**  
**Cu, EPR insulated, individual and overall screen, LSZH outer sheath**  
**IEC60332.3, IEC60754, IEC61034**

---

<b>Type</b>	<b>F-Cu/EPR/IS/OS/LSZH 0,6/1Kv</b>	<b>4X2X 2,5sqmm</b>
	<b>FG7XHOHM1 0,6/1Kv</b>	
<b>Conductor :</b>	Flexible plain copper conductor according to IEC60228 cl.5 size 2,5sqmm ( 48x0,25 ) Diam. 2 mm	
<b>Insulation :</b>	PVC extruded compound	- Temperature range -15 + 70°C
	Thickness : 0,7 mm	- Temperature laying -5 + 70°C
<b>Laying up :</b>	Twisted to pair, color Blue - Black numbered ( or to be agreed )	
<b>Pair/Triad screen</b>	Applied over the single pair/triad will be wrapped with polyester tape and shielded with Aluminum / Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 size 0,5sqmm, over the screen will be placed a further Mylar tape.	
<b>Overall screen</b>	Applied over total assembly will be wrapped with polyester tape and shielded with Aluminum/Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 size 0,5sqmm.	
<b>Outer sheath :</b>	M1, Low Smoke Zero Halogen emission extruded compound	
	Color :	Black ( or to be agreed )
	Thickness :	2,0 mm
	Overall diameter :	19 mm
	Total weight :	550 Kg/Km
<b>Marking :</b>	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
<b>Performance :</b>	- Conductor resistance 7,98 ohm/Km ( + 5% for multipair )	
	- Test voltage core to core 4 Kv	
	- Flame retardant according to IEC60332-3-24, CEI20-22/3	
	- Low smoke and halogen free as per IEC60754-2, CEI20-37/2	
	- Low smoke density emission IEC61034-1/2	
	- Minimum bending radius 8 V. D.	
	- Hydrocarbon and UV resistant	
	- Inductance </= 0,90 mH/Km	
	- Capacitance </= 0,250 microF/Km	

**Weight and diameter are theoretical + / - 10%**