

POWER CABLE
Cu, EPR insulated, LSZH bedding, STA, LSZH outer sheath
IEC60332.3, IEC60754, IEC61034

Type	F-Cu/EPR/LSZH/STA/LSZH 0,6/1Kv	7G 6sqmm
	FG7OM1NM1 0,6/1Kv	
Conductor :	Flexible plain copper conductor according to IEC60228 cl.5 size 6sqmm (80x0,30) Diam. 3 mm	
Insulation :	Cross-linked HEPR extruded compound	- Temperature range -20 + 90°C
	Thickness : 0,7 mm	- Temperature laying -5 + 90°C
Laying up :	Twisted to core, color Y/G - Black numbered (or to be agreed)	
Bedding :	M1, Low Smoke Zero Halogen emission extruded compound	
	Thickness : 1,0 mm	
Armour :	STA, Double galvanized steel tape	
	Thickness : 0,2 mm	
Outer sheath :	M1, Low Smoke Zero Halogen emission extruded compound	
	Color : Black (or to be agreed)	
	Thickness : 2,0 mm	
	Overall diameter : 22 mm	
	Total weight : 1050 Kg/Km	
Marking :	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
Performance :	- Conductor resistance 3,3 ohm/Km (+ 5% for multipair)	
	- Test voltage core to core 3,5 Kv	
	- Flame retardant according to IEC60332-3-24, CEI20-22/3	
	- Low smoke and halogen free as per IEC60754-2, CEI20-37/2	
	- Low smoke density emission IEC61034-1/2	
	- Minimum bending radius 16 V. D.	
	- Hydrocarbon and UV resistant	

Weight and diameter are theoretical + / - 10%