

POWER CABLE
Cu, EPR insulated, LSZH bedding, SWB, LSZH outer sheath
IEC60332.3, IEC60502

Type	F-Cu/EPR/LSZH/SWB/LSZH 0,6/1Kv	3G 2,5sqmm
	FG7OM1AM1 0,6/1Kv	
Conductor :	Flexible plain copper conductor according to IEC60228 cl.5 size 2,5sqmm (48x0,25) Diam. 2 mm	
Insulation :	Cross-linked XLPE extruded compound	- Temperature range -20 + 90°C
	Thickness : 0,7 mm	- Temperature laying -5 + 90°C
Laying up :	Twisted to core, color Blue - Brown - Y/G (or to be agreed)	
Bedding :	M1, Low Smoke Zero Halogen emission extruded compound	
	Thickness : 1,0 mm	
Armour :	SWB, Galvanized steel braid wires	
	Thickness : 0,3 mm	
Outer sheath :	M1, Low Smoke Zero Halogen emission extruded compound	
	Color : Black (or to be agreed)	
	Thickness : 1,8 mm	
	Overall diameter : 14,4 mm	
	Total weight : 340 Kg/Km	
Marking :	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
Performance :	- Conductor resistance 7,98 ohm/Km (+ 5% for multipair)	
	- Test voltage core to core 3,5 Kv	
	- Flame retardant according to IEC60332-3-22, CEI20-22/2	
	- Low smoke and halogen free as per IEC60754-2, CEI20-37/2	
	- Low smoke density emission IEC61034-1/2	
	- Minimum bending radius 12 V. D.	
	- Hydrocarbon and UV resistant	

Weight and diameter are theoretical + / - 10%