

**INSTRUMENTATION CABLE
Cu, EPR insulated, overall screen, LSZH outer sheath
IEC60332.3, IEC60754, IEC61034**

Type	F-Cu/EPR/OS/LSZH 300/500V FG7OHM1 300/500V	4X 0,5sqmm
Conductor :	Flexible plain copper conductor according to IEC60228 cl.5 size 0,5sqmm (16x0,20) Diam. 0,9 mm	
Insulation :	Cross-linked HEPR extruded compound Thickness : 0,5 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
Laying up :	Twisted to core, color Blue - Brown - Black - Gery (or to be agreed)	
Overall screen	Applied over total assembly will be wrapped with polyester tape and shielded with Aluminum/Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 sizq 0,5sqmm.	
Outer sheath :	M1, Low Smoke Zero Halogen emission extruded compound Color : Black (or to be agreed) Thickness : 1,2 mm Overall diameter : 8,4 mm Total weight : 110 Kg/Km	
Marking :	On the outhere sheath " manufacturer's name year & description cable " with ink-jet printer.	
Performance :	- Conductor resistance 39 ohm/Km (+ 5% for multipair) - Test voltage core to core 2 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and halogen free as per IEC60754-2, CEI20-37/2 - Low smoke density emission IEC61034-1/2 - Minimum bending radius 8 V. D. - Hydrocarbon UV resistant - Inductance </= 0,90 mH/Km - Capacitance </= 0,090 microF/Km	

Weight and diameter are theoretical + / - 10%

**INSTRUMENTATION CABLE
Cu, EPR insulated, overall screen, LSZH outer sheath
IEC60332.3, IEC60754, IEC61034**

Type	F-Cu/EPR/OS/LSZH 300/500V FG7OHM1 300/500V	4X 0,5sqmm
Conductor :	Flexible plain copper conductor according to IEC60228 cl.5 size 0,5sqmm (16x0,20) Diam. 0,9 mm	
Insulation :	Cross-linked HEPR extruded compound Thickness : 0,5 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
Laying up :	Twisted to core, color Blue - Brown - Black - Gery (or to be agreed)	
Overall screen	Applied over total assembly will be wrapped with polyester tape and shielded with Aluminum/Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 sizq 0,5sqmm.	
Outer sheath :	M1, Low Smoke Zero Halogen emission extruded compound Color : Black (or to be agreed) Thickness : 1,2 mm Overall diameter : 8,4 mm Total weight : 110 Kg/Km	
Marking :	On the outhere sheath " manufacturer's name year & description cable " with ink-jet printer.	
Performance :	- Conductor resistance 39 ohm/Km (+ 5% for multipair) - Test voltage core to core 2 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and halogen free as per IEC60754-2, CEI20-37/2 - Low smoke density emission IEC61034-1/2 - Minimum bending radius 8 V. D. - Hydrocarbon UV resistant - Inductance </= 0,90 mH/Km - Capacitance </= 0,090 microF/Km	

Weight and diameter are theoretical + / - 10%