

**INSTRUMENTATION CABLE  
Cu, EPR insulated, overall screen, LSZH outer sheath  
IEC60332.3, IEC60754, IEC61034**

---

<b>Type</b>	<b>F-Cu/EPR/OS/LSZH 0,6/1Kv FG7XOHM1 0,6/1Kv</b>	<b>4X2X 0,75sqmm</b>
<b>Conductor :</b>	Flexible plain copper conductor according to IEC60228 cl.5 size 0,75sqmm ( 24x0,20 ) Diam. 1,12 mm	
<b>Insulation :</b>	Cross-linked HEPR extruded compound Thickness : 0,7 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
<b>Laying up :</b>	Twisted to pair, color Blue - Black numbered ( or to be agreed )	
<b>Overall screen</b>	Applied over total assembly will be wrapped with polyester tape and shielded with Aluminum/Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 size 0,5sqmm.	
<b>Outer sheath :</b>	M1, Low Smoke Zero Halogen emission extruded compound Color : Black ( or to be agreed ) Thickness : 1,6 mm Overall diameter : 14 mm Total weight : 240 Kg/Km	
<b>Marking :</b>	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
<b>Performance :</b>	- Conductor resistance 26 ohm/Km ( + 5% for multipair ) - Test voltage core to core 4 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and halogen free as per IEC60754-2, CEI20-37/2 - Low smoke density emission IEC61034-1/2 - Minimum bending radius 10 V. D. - Hydrocarbon and UV resistant  - Inductance </= 0,90 mH/Km - Capacitance </= 0,250 microF/Km  - Max. short circuit temp. 250°C	

**Weight and diameter are theoretical + / - 10%**