

**INSTRUMENTATION CABLE  
Cu, EPR insulated, overall screen, PVC outer sheath  
IEC60332.3**

---

<b>Type</b>	<b>F-Cu/EPR/OS/PVC 0,6/1Kv FG7OHR 0,6/1Kv</b>	<b>2X 2,5sqmm</b>
<b>Conductor :</b>	Flexible red copper conductor according to IEC60228 cl.5 size 2,5sqmm ( 48x0,25 ) Diam. 2 mm	
<b>Insulation :</b>	Cross-linked HEPR extruded compound Thickness : 0,7 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
<b>Laying up :</b>	Twisted to core, color Blue - Brown	
<b>Overall screen</b>	Over the multipair will be shielded with aluminum/mylar tape, with tinned copper drain wire 7x0,30 placed between the aluminum/myler tape and further mylar tape.	
<b>Bedding :</b>	Thickness : mm	
<b>Armor :</b>	Thickness : mm	
<b>Outer sheath :</b>	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Green ( or to be agreed ) Thickness : 1,6 mm Overall diameter : 11 mm Total weight : 180 Kg/Km	
<b>Marking :</b>	On the outhter sheath " manufacturer's name year & description cable " with ink-jet printer.	
<b>Performance :</b>	- Conductor resistance 7,98 ohm/Km (+ 5% for multipair ) - Test voltage core to core 4 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and fume as per IEC60754-1, CEI20-37 - HCL emission <= 22% - Minimum bending radius 8 V. D. - Hydrocarbon resistant	

**Weight and diameter are theoretical +/- 10%**