

**POWER CABLE  
Cu, EPR insulated, PVC outer sheath  
IEC60332.3**

---

<b>Type</b>	<b>F-Cu/EPR/PVC 0,6/1Kv FG7OR 0,6/1Kv</b>	<b>12X 16AWG</b>
<b>Conductor :</b>	Flexible plain copper conductor according to IEC60228 cl.5 size 16AWG Diam. 1,55 mm	
<b>Insulation :</b>	Cross-linked HEPR extruded compound Thickness : 0,7 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
<b>Laying up :</b>	Twisted to core, color Black numbered ( or to be agreed )	

<b>Outer sheath :</b>	PVC, Polyvinylchloride Low Smoke and Fume extruded compound	
Color :	Black ( or to be agreed )	
Thickness :	2,0 mm	
Overall diameter :	17 mm	
Total weight :	440 Kg/Km	

**Marking :**

On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.

<b>Performance :</b>	- Conductor resistance	13,3 ohm/Km	( + 5% for multipair )
	- Test voltage core to core	4 Kv	
	- Flame retardant according to IEC60332-3-24, CEI20-22/3		
	- Low smoke and fume as per IEC60754-1, CEI20-37		
	- HCL emission $\leq$ 22%		
	- Minimum bending radius	8 V. D.	
	- Hydrocarbon UV resistant		
	- Inductance $\leq$	0,90 mH/Km	
	- Capacitance $\leq$	0,250 microF/Km	

**Weight and diameter are theoretical + / - 10%**