

**POWER CABLE
Cu, EPR insulated, PVC outer sheath
IEC60332.3**

Type	F-Cu/EPR/PVC 0,6/1Kv FG7OR 0,6/1Kv	2X 16AWG
Conductor :	Flexible plain copper conductor according to IEC60228 cl.5 size 16AWG Diam. 1,55 mm	
Insulation :	Cross-linked HEPR extruded compound Thickness : 0,7 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
Laying up :	Twisted to pair, color Brown - Blue (or to be agreed)	

Outer sheath :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound	
Color :	Black (or to be agreed)	
Thickness :	1,8 mm	
Overall diameter :	9,4 mm	
Total weight :	120 Kg/Km	

Marking :

On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.

Performance :	- Conductor resistance	13,3 ohm/Km	(+ 5% for multipair)
	- Test voltage core to core	4 Kv	
	- Flame retardant according to IEC60332-3-24, CEI20-22/3		
	- Low smoke and fume as per IEC60754-1, CEI20-37		
	- HCL emission </= 22%		
	- Minimum bending radius	8 V. D.	
	- Hydrocarbon UV resistant		
	- Inductance </=	0,90 mH/Km	
	- Capacitance </=	0,250 microF/Km	

Weight and diameter are theoretical + / - 10%