

**POWER CABLE
Cu, EPR insulated, PVC bedding, GST, PVC outer sheath
IEC60332.3, IEC60502**

Type	F-Cu/EPR/PVC/GST/PVC 0,6/1Kv FG7ORNR 0,6/1Kv	4G 4sqmm
Conductor :	Flexible red copper conductor according to IEC60228 cl.5 size Diam. 2,5 mm	4sqmm (56x0,30)
Insulation :	Cross-linked HEPR extruded compound Thickness : 0,7 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
Laying up :	Twisted to core, color Y/G - Brown - Black - Grey (or to be agreed)	

Overall screen

Bedding :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Thickness : 1,0 mm
Armor :	STA, Double galvanized steel tape Thickness : 0,20 mm
Outer sheath :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Black (or to be agreed) Thickness : 1,6 mm Overall diameter : 17 mm Total weight : 570 Kg/Km

Marking :

On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.

Performance :	- Conductor resistance 4,95 ohm/Km (+ 5% for multipair)
	- Test voltage core to core 4 Kv
	- Flame retardant according to IEC60332-3-24, CEI20-22/3
	- Low smoke and fume as per IEC60754-1, CEI20-37
	- HCL emission <= 22%
	- Minimum bending radius 12 V. D.
	- Hydrocarbon resistant

Weight and diameter are theoretical +/- 10%