

**POWER CABLE
Cu, EPR insulated, PVC bedding, SWB, PVC outer sheath
IEC60332.3, IEC60502**

Type	F-Cu/EPR/PVC/SWB/PVC 0,6/1Kv FG7ORAR 0,6/1Kv	16G 1,5sqmm
Conductor :	Flexible red copper conductor according to IEC60228 cl.5 size 1,5sqmm (28x0,25) Diam. 1,55 mm	
Insulation :	Cross-linked HEPR extruded compound Thickness : 0,7 mm	- Temperature range -40 + 90°C - Temperature laying -5 + 90°C
Laying up :	Twisted to core, color Y/G - Black numbered (or to be agreed)	

Overall screen

Bedding :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Thickness : 1,0 mm	
Armor :	SWB, Galvanized steel braid wires Thickness : 0,3 mm	
Outer sheath :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound, Artic -40°C Color : Grey (or to be agreed) Thickness : 2,0 mm Overall diameter : 22 mm Total weight : 890 Kg/Km	

Marking :

On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.

Performance :	- Conductor resistance	13,3 ohm/Km	(+ 5% for multipair)
	- Test voltage core to core	4 Kv	
	- Flame retardant according to IEC60332-3-24, CEI20-22/3		
	- Low smoke and fume as per IEC60754-1, CEI20-37		
	- HCL emission </= 22%		
	- Minimum bending radius	10 V. D.	
	- Hydrocarbon resistant		

Weight and diameter are theoretical + / - 10%