

**POWER CABLE**  
**Cu, EPR insulated, PVC bedding, SWB, PVC outer sheath**  
**IEC60332.3**

---

<b>Type</b>	<b>F-Cu/EPR/PVC/SWB/PVC 0,6/1Kv</b>	<b>4G 16sqmm</b>
	<b>FG7ORAR 0,6/1Kv</b>	
<b>Conductor :</b>	Flexible plain copper conductor according to IEC60228 cl.5 size 16sqmm Diam. 5,2 mm	
<b>Insulation :</b>	Cross-linked HEPR extruded compound	- Temperature range -20 + 90°C
	Thickness : 0,7 mm	- Temperature laying -5 + 90°C
<b>Laying up :</b>	Twisted to pair, color Y/G - Brown - Black - Grey ( or to be agreed )	

**Bedding :** PVC, Polyvinylchloride Low Smoke and Fume extruded compound  
Thickness : 1,0 mm

**Armour :** SWB, Galvanized steel braid wires  
Thickness : 0,3 mm

**Outer sheath :** PVC, Polyvinylchloride Low Smoke and Fume extruded compound  
Color : Black ( or to be agreed )  
Thickness : 2,0 mm  
Overall diameter : 27 mm  
Total weight : 1200 Kg/Km

**Marking :**  
On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.

**Performance :**

- Conductor resistance 1,21 ohm/Km (+ 5% for multipair )
- Test voltage core to core 4 Kv
- Flame retardant according to IEC60332-3-24, CEI20-22/3
- Low smoke and fume as per IEC60754-1, CEI20-37
- HCL emission  $\leq$  22%
- Minimum bending radius 12 V. D.
- Hydrocarbon UV resistant
  
- Inductance  $\leq$  0,90 mH/Km
- Capacitance  $\leq$  0,250 microF/Km

**Weight and diameter are theoretical + / - 10%**