

**FIRE RESISTANT INSTRUMENTATION CABLE  
CuMGT, EPR insulated, LSZH bedding, SWB, LSZH outer sheath  
IEC60332.3, IEC60754, IEC61034, IEC60331-21**

---

<b>Type</b>	<b>F-CuMGT/EPR/LSZH/SWB/LSZH 0,6/1Kv FTG100M1AM1 0,6/1Kv</b>	<b>2X 2,5sqmm</b>
<b>Conductor :</b>	Flexible plain copper conductor according to IEC60228 cl.5 size 2,5sqmm ( 48x0,25 ) Diam. 2 mm	
<b>Insulation :</b>	Mica tape, Cross-linked G10 extruded compound Thickness : 0,7 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
<b>Laying up :</b>	Twisted to pair, Blue - Black ( or to be agreed )	
<b>Pair screen</b>		
<b>Overall screen</b>		
<b>Bedding :</b>	M1, Low Smoke Zero Halogen emission extruded compound Thickness : 1,0 mm	
<b>Armour :</b>	SWB, Galvanized steel braid wires Thickness : 0,3 mm	
<b>Outer sheath :</b>	M1, Low Smoke Zero Halogen emission extruded compound Colour : Black ( or to be agreed ) Thickness : 1,8 mm Overall diameter : 15,8 mm Total weight : 420 Kg/Km	
<b>Marking :</b>	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
<b>Performance :</b>	- Conductor resistance 7,98 ohm/Km (+ 5% for multipair ) - Test voltage core to core 3,5 Kv - Flame retardant according to IEC60332.3-22, CEI20-22/2 - Low smoke and halogen free as per IEC60754-2, CEI20-37/2 - Fire resistant IEC60331-21 - Minimum bending radius 16 v.d. - Hydrocarbon UV resistant	