

**FIRE RESISTANT INSTRUMENTATION CABLE  
CuMGT, G10 insulated, LSZH bedding, CWB, LSZH outer sheath  
IEC60332.3, IEC60754, IEC61034, IEC60331-21**

---

<b>Type</b>	<b>F-Cu/MGT/G10/LSZH/CWB/LSZH 0,6/1Kv FTG100H2M1 0,6/1Kv</b>	<b>5G 2,5sqmm</b>
<b>Conductor :</b>	Flexible plain copper conductor according to IEC60228 cl.5 size 2,5sqmm ( 48x0,25 ) Diam. 2 mm	
<b>Insulation :</b>	Mica tape, Cross-linked G10 extruded compound Thickness : 0,7 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
<b>Laying up :</b>	Twisted to core, Blue - Brown - Black - Grey - Y/G ( or to be agreed )	
<b>Pair screen</b>		
<b>Overall screen</b>		
<b>Bedding :</b>	PET plus MGT tape Thickness : mm	
<b>Screen :</b>	CWB plain copper wire braid Thickness : 0,2 mm	
<b>Outer sheath :</b>	M1, Low Smoke Zero Halogen emission extruded compound Colour : Black Thickness : 1,8 mm Overall diameter : 17 mm Total weight : 480 Kg/Km	
<b>Marking :</b>	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
<b>Performance :</b>	- Conductor resistance 7,98 ohm/Km (+ 5% for multipair ) - Test voltage core to core 3,5 Kv - Flame retardant according to IEC60332.3-22, CEI20-22/2 - Low smoke and halogen free as per IEC60754-2, CEI20-37/2 - Fire resistant IEC60331-21 - Minimum bending radius 18 v.d. - Hydrocarbon and UV resistant	