

FIRE RESISTANT INSTRUMENTATION CABLE
CuMGT, XLPE insulated, LSZH bedding, SWA, LSZH outer sheath
IEC60332.3, IEC60754, IEC61034, IEC60331-23

Type	F-CuMGT/XLPE/LSZH/SWA/LSZH 0,6/1Kv FTE40M1FM1 0,6/1Kv	3x 2,5sqmm
Conductor :	Flexible red copper conductor according to IEC60228 cl.5 size Diam. 2 mm	2,5sqmm (48x0,25)
Insulation :	Mica tape, Cross-linked XLPE extruded compound Thickness : 0,7 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
Laying up :	Twisted to core, Brown - Black - Grey (or to be agreed)	
Pair screen		
Overall screen		
Bedding :	M1, Low Smoke Zero Halogen emission extruded compound Thickness : 1,0 mm	
Armour :	SWA, Galvanized steel round wires Thickness : 0,9 mm	
Outer sheath :	M1, Low Smoke Zero Halogen emission extruded compound Colour : Black (or to be agreed) Thickness : 1,6 mm Overall diameter : 16,4 mm Total weight : 360 Kg/Km	
Marking :	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
Performance :	- Conductor resistance 7,98 ohm/Km (+ 5% for multipair) - Test voltage core to core 4 Kv - Flame retardant according to IEC60332.3-22, CEI20-22/2 - Low smoke and halogen free as per IEC60754-2, CEI20-37/2 - Fire resistant IEC60331-23 - Minimum bending radius 16 v.d.	