

**INSTRUMENTATION CABLE  
Cu, PE insulated, overall screen, PVC outer sheath  
IEC60332.1, CEI20-35, EN50288-7**

---

<b>Type</b>	<b>F-Cu/PE/OS/PVC 450/750V FEOHR 450/750V</b>	<b>12X 0,75sqmm</b>
<b>Conductor :</b>	Flexible plain copper conductor according to IEC60228 cl.5 size 0,75sqmm ( 24x0,20 ) Diam. 1,12 mm	
<b>Insulation :</b>	Polyethylene extruded compound Thickness : 0,6 mm	- Temperature range -20 + 70°C - Temperature laying -5 + 70°C
<b>Laying up :</b>	Twisted to core, color Black numbered ( or to be agreed )	
<b>Overall screen</b>	Applied over total assembly will be wrapped with polyester tape and shielded with Aluminum/Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 size 0,5sqmm.	
<b>Outer sheath :</b>	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Blue ( or to be agreed ) Thickness : 1,6 mm Overall diameter : 13 mm Total weight : 270 Kg/Km	
<b>Marking :</b>	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
<b>Performance :</b>	<ul style="list-style-type: none"><li>- Conductor resistance 26 ohm/Km ( + 5% for multipair )</li><li>- Test voltage core to core 3 Kv</li><li>- Flame retardant according to IEC60332.1, CEI20-35</li><li>- Low smoke and fume as per IEC60754-1, CEI20-37</li><li>- HCL emission <math>\leq</math> 22%</li><li>- Minimum bending radius 8 V. D.</li><li>- Hydrocarbon resistant</li><li>- Cable for intrinsically safe application</li><li>- Inductance <math>\leq</math> 0,90 mH/Km</li><li>- Capacitance <math>\leq</math> 0,075 microF/Km</li><li>- This cable is suitable to be used in ATEX area following the EN60079-14 prescription</li></ul>	

**Weight and diameter are theoretical + / - 10%**