

**INSTRUMENTATION CABLE
Cu, PE insulated, overall screen, PVC outer sheath
IEC60332.1, CEI20-35, EN50288-7**

Type	F-Cu/PE/OS/PVC 450/750V FEOHR 450/750V	6X 0,75sqmm
Conductor :	Flexible plain copper conductor according to IEC60228 cl.5 size 0,75sqmm (24x0,20) Diam. 1,12 mm	
Insulation :	Polyethylene extruded compound Thickness : 0,6 mm	- Temperature range -20 + 70°C - Temperature laying -5 + 70°C
Laying up :	Twisted to core, color Black numbered (or to be agreed)	
Overall screen	Applied over total assembly will be wrapped with polyester tape and shielded with Aluminum/Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 size 0,5sqmm.	
Outer sheath :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Blue (or to be agreed) Thickness : 1,4 mm Overall diameter : 10,5 mm Total weight : 170 Kg/Km	
Marking :	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
Performance :	- Conductor resistance 26 ohm/Km (+ 5% for multipair) - Test voltage core to core 3 Kv - Flame retardant according to IEC60332.1, CEI20-35 - Low smoke and fume as per IEC60754-1, CEI20-37 - HCL emission <= 22% - Minimum bending radius 8 V. D. - Hydrocarbon resistant - Cable for intrinsically safe application - Inductance <= 0,90 mH/Km - Capacitance <= 0,075 microF/Km - This cable is suitable to be used in ATEX area following the EN60079-14 prescription	

Weight and diameter are theoretical + / - 10%