

**INSTRUMENTATION CABLE  
Cu, PVC insulated, CWB screen, PVC outer sheath  
IEC60332.3, EN50288-7**

---

<b>Type</b>	<b>F-Cu/PVC/CWB/PVC 300/500V Li-YCY</b>	<b>4X2X 0,5sqmm</b>
<b>Conductor :</b>	Flexible red copper conductor according to IEC60228 cl.5 size 0,5sqmm ( 16x0,20 ) Diam. 0,9 mm	
<b>Insulation :</b>	PVC extruded compound Thickness : 0,6 mm	- Temperature range -15 + 70°C - Temperature laying -5 + 70°C
<b>Laying up :</b>	Twisted to pairs, color White-Brown, Green-Yellow, Grey-Pink, Blue-Red	

**Overall screen**

<b>Bedding :</b>	PET tape Thickness : mm	
<b>Screen :</b>	CWB tinned copper wire braid Thickness : mm	
<b>Outer sheath :</b>	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Grey ( or to be agreed ) Thickness : 1,4 mm Overall diameter : 13 mm Total weight : 230 Kg/Km	

**Marking :**

On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.

<b>Performance :</b>	- Conductor resistance	39 ohm/Km	( + 5% for multipair )
	- Test voltage core to core	2 Kv	
	- Flame retardant according to IEC60332-3-24, CEI20-22/3		
	- Low smoke and fume as per IEC60754-1, CEI20-37		
	- HCL emission <= 22%		
	- Minimum bending radius	8 V. D.	
	- Hydrocarbon resistant		

**Weight and diameter are theoretical + / - 10%**