

INSTRUMENTATION CABLE**Cu, PVC insulated, individual and overall screen, PVC outer sheath
IEC60332.1, IEC60332.3**

Type **F-Cu/PVC/IS/OS/PVC 450/750V
FR2XHOHR 450/750V****Conductor :** Flexible plain copper conductor according to IEC60228 cl.5 size 1sqmm (32x0,20)
Diam. 1,3 mm**Insulation :** PVC extruded compound - Temperature range -15 + 80°C
Thickness : 0,6 mm - Temperature laying -5 + 70°C**Laying up :** Twisted to pair, Blue - Black numbered (or to be agreed)**Pair/Triad screen** Applied over the single pair/triad will be wrapped with polyester tape and shielded with Aluminum / Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 sizq 0,5sqmm, over the screen will be placed a further Mylar tape.**Overall screen** Applied over total assembly will be wrapped with polyester tape and shielded with Aluminum/Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 sizq 0,5sqmm.**Outer sheath :** PVC, Polyvinylchloride Low Smoke and Fume extruded compound
Color : Grey**Marking :**

On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.

Performance :

- Conductor resistance 19,5 ohm/Km (+ 5% for multipair)
- Test voltage core to core 3 Kv
- Flame retardant according to IEC60332-3-24, CEI20-22/3
- Low smoke and fume as per IEC60754-1, CEI20-37
- HCL emission <= 22%
- Hydrocarbon resistant

- Inductance <= 0,90mH/Km
- Capacitance <= 0,25microF/Km

