

**INSTRUMENTATION CABLE**  
**Cu, PVC insulated, individual and overall screen, PVC outer sheath**  
**IEC60332.3, CEI20-22/2**

---

<b>Type</b>	<b>Cu-CI5/PVC/IS/OS/PVC 450/750V FR2XHOHR 450/750V</b>	<b>6X2X 1,5sqmm</b>
<b>Conductor :</b>	Flexible red copper conductor according to IEC60228 cl.5 size 1,5sqmm ( 28x0,25 ) Diam. 1,55 mm	
<b>Insulation :</b>	PVC extruded compound Thickness : 0,7 mm	- Temperature range -15 + 70°C - Temperature laying -5 + 70°C
<b>Laying up :</b>	Twisted to pair, color Blue - Black numbered	
<b>Pair/Triad screen</b>	Each pair will be shielded with aluminium/mylar tape, with tinned copper drain wire 7x0,30 placed between the aluminium/mylar tape and further mylar tape. Each pair will be shielded with aluminium/mylar tape, with tinned copper drain wire 7x0,20	
<b>Overall screen</b>	Over the multipair will be shielded with aluminium/mylar tape, with tinned copper drain wire 7x0,30 placed between the aluminium/mylar tape and further mylar tape. Over the multipair will be shielded with aluminium/mylar tape, with tinned copper drain	
<b>Outer sheath :</b>	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Gery Thickness : 2,0 mm Overall diameter : 20 mm Total weight : 570 Kg/Km	
<b>Marking :</b>	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
<b>Performance :</b>	- Conductor resistance 13,3 ohm/Km ( + 5% for multipair ) - Test voltage core to core 3 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and fume as per IEC60754-1, CEI20-37 - HCL emission <= 22% - Minimum bending radius 8 V. D. - Hydrocarbon resistant  - Inductance <= 0,90mH/Km - Capacitance <= 0,20microF/Km	

**Weight and diameter are theoretical + / - 10%**