

**INSTRUMENTATION CABLE
Cu, PVC insulated, overall screen, PVC outer sheath
IEC60332.3, CEI20-22/2**

Type	Cu-CI5/PVC/OS/PVC 450/750V FR2XOHR 450/750V	12X2X 1,5sqmm
Conductor :	Flexible red copper conductor according to IEC60228 cl.5 size 1,5sqmm (28x0,25) Diam. 1,55 mm	
Insulation :	PVC extruded compound Thickness : 0,7 mm	- Temperature range -15 + 70°C - Temperature laying -5 + 70°C
Laying up :	Twisted to core, color Blue - Black numbered	

Overall screen Over the multipair will be shielded with aluminium/mylar tape, with tinned copper drain wire 7x0,30 placed between the aluminium/mylar tape and further mylar tape.
Over the multipair will be shielded with aluminium/mylar tape, with tinned copper drain

Outer sheath : PVC, Polyvinylchloride Low Smoke and Fume extruded compound
Color : Grey
Thickness : 2,0 mm
Overall diameter : 25 mm
Total weight : 850 Kg/Km

Marking :

On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.

Performance :

- Conductor resistance 13,3 ohm/Km (+ 5% for multipair)
- Test voltage core to core 3 Kv
- Flame retardant according to IEC60332-3-24, CEI20-22/3
- Low smoke and fume as per IEC60754-1, CEI20-37
- HCL emission <= 22%
- Minimum bending radius 8 V. D.
- Hydrocarbon resistant

- Inductance <= 0,90mH/Km
- Capacitance <= 0,20microF/Km

Weight and diameter are theoretical + / - 10%