

**INSTRUMENTATION CABLE  
Cu, PVC insulated, overall screen, PVC outer sheath  
IEC60332.3, CEI20-22/2**

---

<b>Type</b>	<b>F-Cu/PVC/OS/PVC 450/750V FR2XOHR 450/750V</b>	<b>12X2X 2,5sqmm</b>
<b>Conductor :</b>	Flexible plain copper conductor according to IEC60228 cl.5 size 2,5sqmm ( 48x0,25 ) Diam. 2 mm	
<b>Insulation :</b>	PVC extruded compound Thickness : 0,7 mm	- Temperature range -15 + 70°C - Temperature laying -5 + 70°C
<b>Laying up :</b>	Twisted to pair, color Blue - Black numbered ( or to be agreed )	
<b>Overall screen</b>	Applied over total assembly will be wrapped with polyester tape and shielded with Aluminum/Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 size 0,5sqmm.	
<b>Outer sheath :</b>	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Grey ( or to be agreed ) Thickness : 2,0 mm Overall diameter : 29 mm Total weight : 1150 Kg/Km	
<b>Marking :</b>	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
<b>Performance :</b>	- Conductor resistance 7,98 ohm/Km ( + 5% for multipair ) - Test voltage core to core 3 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and fume as per IEC60754-1, CEI20-37 - HCL emission <= 22% - Minimum bending radius 10 V. D. - Hydrocarbon resistant  - Inductance <= 0,90 mH/Km - Capacitance <= 0,250 microF/Km	

**Weight and diameter are theoretical + / - 10%**