

**INSTRUMENTATION CABLE
Cu, PVC insulated, overall screen, PVC outer sheath
IEC60332.3, EN50288-7**

Type	F-Cu/PVC/OS/PVC 300/500V FR2XOHR 300/500V	4X3X 0,75sqmm
Conductor :	Flexible red copper conductor according to IEC60228 cl.5 size 0,75sqmm (24x0,20) Diam. 1,12 mm	
Insulation :	PVC extruded compound Thickness : 0,6 mm	- Temperature range -15 + 70°C - Temperature laying -5 + 70°C
Laying up :	Twisted to pairs, color Blue - Brown - Black numbered (or to be agreed)	
Overall screen	Over the multipair will be shielded with aluminum/mylar tape, with tinned copper drain wire 7x0,30 placed between the aluminum/mylar tape and further mylar tape.	
Bedding :	Thickness : mm	
Armor :	Thickness : mm	
Outer sheath :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Black (or to be agreed) Thickness : 1,6 mm Overall diameter : 16 mm Total weight : 340 Kg/Km	
Marking :	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
Performance :	- Conductor resistance 26 ohm/Km (+ 5% for multipair) - Test voltage core to core 2 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and fume as per IEC60754-1, CEI20-37 - HCL emission <= 22% - Minimum bending radius 8 V. D. - Hydrocarbon resistant	

Weight and diameter are theoretical + / - 10%