

**INSTRUMENTATION CABLE
Cu, PVC insulated, overall screen, PVC outer sheath
IEC60332.3, EN50288-7**

Type	F-Cu/PVC/OS/PVC 300/500V FR2OHR 300/500V	6X 0,75sqmm
Conductor :	Flexible red copper conductor according to IEC60228 cl.5 size 0,75sqmm (24x0,20) Diam. 1,12 mm	
Insulation :	PVC extruded compound Thickness : 0,45 mm	- Temperature range -15 + 70°C - Temperature laying -5 + 70°C
Laying up :	Twisted to core, color Black numbered (or to be agreed)	

Overall screen Over the multipair will be shielded with aluminium/mylar tape, with tinned copper drain wire 7x0,30 placed between the aluminium/mylar tape and further mylar tape.
Over the multipair will be shielded with aluminium/mylar tape, with tinned copper drain

Outer sheath : PVC, Polyvinylchloride Low Smoke and Fume extruded compound
Color : Blue
Thickness : 1,4 mm
Overall diameter : 9,8 mm
Total weight : 160 Kg/Km

Marking :

On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.

Performance :

- Conductor resistance 26 ohm/Km (+ 5% for multipair)
- Test voltage core to core 2 Kv
- Flame retardant according to IEC60332-3-24, CEI20-22/3
- Low smoke and fume as per IEC60754-1, CEI20-37
- HCL emission \leq 22%
- Minimum bending radius 8 V. D.
- Hydrocarbon resistant

- Inductance \leq 0,90mH/Km
- Capacitance \leq 0,20microF/Km

Weight and diameter are theoretical + / - 10%