

**INSTRUMENTATION CABLE**  
**Cu, PVC insulated, overall screen, PVC bedding, SWB, PVC outer sheath**  
**IEC60332.1, IEC60332.3**

---

<b>Type</b>	<b>F-Cu/PVC/OS/PVC/SWB/PVC 450/750V</b> <b>FR2OHRAR 450/750V</b>	
<b>Conductor :</b>	Flexible red copper conductor according to IEC60228 cl.5 size 1,5sqmm ( 28x0,25 ) Diam. 1,55 mm	
<b>Insulation :</b>	PVC extruded compound Thickness : 0,7 mm	- Temperature range -15 + 105°C - Temperature laying -5 + 70°C
<b>Laying up :</b>	Twisted to core, color Blue - Black, Blue - Black - Brown ( or to be agreed )	
<b>Pair screen</b>		
<b>Overall screen</b>	Over the multipair will be shielded with aluminium/mylar tape, with tinned copper drain wire 7x0,30 placed between the aluminium/mylar tape and further mylar tape.	
<b>Bedding :</b>	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Thickness : 1,0 mm	
<b>Armor :</b>	SWB, Galvanized steel braid wires	
<b>Outer sheath :</b>	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Black / Orange ( or to be agreed )	
<b>Marking :</b>	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
<b>Performance :</b>	- Conductor resistance 13,3 ohm/Km ( + 5% for multipair ) - Test voltage core to core 3 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and fume as per IEC60754-1, CEI20-37 - HCL emission <= 22% - Hydrocarbon and UV resistant	

