

INSTRUMENTATION CABLE**Cu, PVC insulated, overall screen, PVC bedding, SWB, PVC outer sheath
MEU817.02 BK32, CEI20-22/2**

Type **F-Cu/PVC/OS/PVC/SWB/PVC 450/750V
FR2OHRAR 450/750V****Conductor :** Flexible plain copper conductor according to IEC60228 cl.5 size 1,5sqmm (28x0,25)
Diam. 1,55 mm**Insulation :** PVC extruded compound - Temperature range -15 + 80°C
Thickness : 0,8 mm - Temperature laying -5 + 70°C**Laying up :** Twisted to core, Blue - Black, Blue - Black - Brown (or to be agreed)**Overall screen** Applied over total assembly will be wrapped with polyester tape and shielded with Aluminum/Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 size 0,5sqmm.**Bedding :** PVC, Polyvinylchloride Low Smoke and Fume extruded compound
Thickness : 1,0 mm**Armour :** SWB, Galvanized steel braid wires**Outer sheath :** PVC, Polyvinylchloride Low Smoke and Fume extruded compound
Color : Black (or to be agreed)**Marking :**

On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.

Performance :

- Conductor resistance 13,3 ohm/Km (+ 5% for multipair)
- Test voltage core to core 3 Kv
- Flame retardant according to IEC60332-3-24, CEI20-22/3
- Low smoke and fume as per IEC60754-1, CEI20-37
- HCL emission \leq 22%
- Hydrocarbon and UV resistant

- Inductance \leq 0,90 mH/Km
- Capacitance \leq 0,140 microF/Km