

**POWER CABLE
Cu, PVC insulated, PVC outer sheath
IEC60332.3, CEI20-22/2**

Type	F-Cu/PVC/PVC 0,6/1Kv FR2OR 0,6/1Kv	3G 16sqmm
Conductor :	Flexible red copper conductor according to IEC60228 cl.5 size 16sqmm (7X18X0,40) Diam. 5,2 mm	
Insulation :	PVC extruded compound Thickness : 1 mm	- Temperature range -15 + 70°C - Temperature laying -5 + 70°C
Laying up :	Twisted to core, color Y/G - Blue - Black (or to be agreed)	

Overall screen**Bedding :**

Thickness : mm

Armor :

Thickness : mm

Outer sheath : PVC, Polyvinylchloride Low Smoke and Fume extruded compound
Color : Black (or to be agreed)
Thickness : 2,0 mm
Overall diameter : 21 mm
Total weight : 780 Kg/Km

Marking :

On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.

Performance :

- Conductor resistance 1,21 ohm/Km (+ 5% for multipair)
- Test voltage core to core 3,5 Kv
- Flame retardant according to IEC60332-3-24, CEI20-22/3
- Low smoke and fume as per IEC60754-1, CEI20-37
- HCL emission <= 22%
- Minimum bending radius 8 V. D.
- Hydrocarbon resistant

Weight and diameter are theoretical +/- 10%