

**POWER CABLE
Cu, PVC insulated, PVC outer sheath
IEC60332.3, ENI0184**

Type	Cu/PVC/PVC 0,6/1Kv FR2OR 0,6/1Kv	3G 4sqmm
Conductor :	Flexible plain copper conductor according to IEC60228 cl.5 size 4sqmm (56x0,30) Diam. 2,5 mm	
Insulation :	PVC extruded compound Thickness : 0,9 mm	- Temperature range -15 + 70°C - Temperature laying -5 + 70°C
Laying up :	Twisted to core, color Blue - Brown - Y/G (or to be agreed)	

Outer sheath :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound	
Color :	Black (or to be agreed)	
Thickness :	1,6 mm	
Overall diameter :	13 mm	
Total weight :	280 Kg/Km	

Marking :

On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.

Performance :	- Conductor resistance	4,95 ohm/Km	(+ 5% for multipair)
	- Test voltage core to core	4 Kv	
	- Flame retardant according to IEC60332-3-24, CEI20-22/3		
	- Low smoke and fume as per IEC60754-1, CEI20-37		
	- HCL emission \leq 22%		
	- Minimum bending radius	10 V. D.	
	- Hydrocarbon resistant		

Weight and diameter are theoretical + / - 10%