

**POWER CABLE  
Cu, PVC insulated, PVC outer sheath  
IEC60332.3-24, IEC60502**

---

<b>Type</b>	<b>F-Cu/PVC/PVC 0,6/1Kv FR2OR 0,6/1Kv</b>	<b>5G 2,5sqmm</b>
<b>Conductor :</b>	Flexible plain copper conductor according to IEC60228 cl.5 size 2,5sqmm ( 48x0,25 ) Diam. 2 mm	
<b>Insulation :</b>	PVC extruded compound Thickness : 0,9 mm	- Temperature range -15 + 90°C - Temperature laying -5 + 70°C
<b>Laying up :</b>	Twisted to core, color Y/G - Blue - Brown - Black - Grey ( or to be agreed )	

<b>Outer sheath :</b>	PVC, Polyvinylchloride Low Smoke and Fume extruded compound	
Color :	Black ( or to be agreed )	
Thickness :	1,8 mm	
Overall diameter :	13,7 mm	
Total weight :	320 Kg/Km	

**Marking :**

On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.

<b>Performance :</b>	- Conductor resistance	7,98 ohm/Km	( + 5% for multipair )
	- Test voltage core to core	3,5 Kv	
	- Flame retardant according to IEC60332-3-24, CEI20-22/3		
	- Low smoke and fume as per IEC60754-1, CEI20-37		
	- HCL emission <= 22%		
	- Minimum bending radius	8 V. D.	
	- Hydrocarbon and UV resistant		

**Weight and diameter are theoretical + / - 10%**