

POWER CABLE
Cu, PVC insulated, PVC bedding, SWA, PVC outer sheath
IEC60332.3, IEC60502

Type	F-Cu/PVC/PVC/SWA/PVC 0,6/1Kv	2X 2,5sqmm
	FR2ORFR 0,6/1Kv	
Conductor :	Flexible plain copper conductor according to IEC60228 cl.5 size 2,5sqmm (48x0,25) Diam. 2 mm	
Insulation :	PVC extruded compound	- Temperature range -15 + 70°C
	Thickness : 0,9 mm	- Temperature laying -5 + 70°C
Laying up :	Twisted to pair, color Black numbered (or to be agreed)	
Bedding :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound	
	Thickness : 1,0 mm	
Armour :	SWA, Galvanized steel round wires	
	Thickness : 0,9 mm	
Outer sheath :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound	
	Color : Black (or to be agreed)	
	Thickness : 1,8 mm	
	Overall diameter : 14,6 mm	
	Total weight : 340 Kg/Km	
Marking :	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
Performance :	- Conductor resistance 7,98 ohm/Km (+ 5% for multipair)	
	- Test voltage core to core 3,5 Kv	
	- Flame retardant according to IEC60332-3-24, CEI20-22/3	
	- Low smoke and fume as per IEC60754-1, CEI20-37	
	- HCL emission <= 22%	
	Minimum bending radius 14	V. D.
	- Hydrocarbon and UV resistant	

Weight and diameter are theoretical +/- 10%