

**POWER CABLE**  
**Cu, PVC insulated, PVC bedding, SWA, PVC outer sheath**  
**IEC60332.3, CEI20-22/3**

---

<b>Type</b>	<b>F-Cu/PVC/PVC/SWA/PVC 450/750V FR2ORFR 450/750V</b>	<b>3G 2,5sqmm</b>
<b>Conductor :</b>	Flexible plain copper conductor according to IEC60228 cl.5 size 2,5sqmm ( 48x0,25 ) Diam. 2 mm	
<b>Insulation :</b>	PVC extruded compound Thickness : 0,8 mm	- Temperature range -15 + 70°C - Temperature laying -5 + 70°C
<b>Laying up :</b>	Twisted to core, color White - Black - Y/G ( or to be agreed )	
<b>Bedding :</b>	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Thickness : 1,0 mm	
<b>Armour :</b>	SWA Galvanized steel round wires with an open helix of galvanized steel tape over the wire Thickness : 0,9 mm	
<b>Outer sheath :</b>	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Blue ( or to be agreed ) Thickness : 1,6 mm Overall diameter : 15 mm Total weight : 350 Kg/Km	
<b>Marking :</b>	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
<b>Performance :</b>	- Conductor resistance 7,98 ohm/Km ( + 5% for multipair ) - Test voltage core to core 3 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and fume as per IEC60754-1, CEI20-37 - HCL emission <= 22% - Minimum bending radius 14 V. D. - Hydrocarbon resistant	

**Weight and diameter are theoretical + / - 10%**