

**INSTRUMENTATION CABLE
Cu, PVC insulated, PVC bedding, SWB, PVC outer sheath
IEC60332.3, CEI20-22/3**

Type	F-Cu/PVC/PVC/SWB/PVC 300/500V FR2ORAR 300/500V	16X 0,75sqmm
Conductor :	Flexible plain copper conductor according to IEC60228 cl.5 size 0,75sqmm (24x0,20) Diam. 1,12 mm	
Insulation :	PVC extruded compound Thickness : 0,6 mm	- Temperature range -15 + 70°C - Temperature laying -5 + 70°C
Laying up :	Twisted to core, color Black numbered (or to be agreed)	

Bedding : PVC, Polyvinylchloride Low Smoke and Fume extruded compound
Thickness : 1,0 mm

Armour : SWB, Galvanized steel braid wires
Thickness : 0,3 mm

Outer sheath : PVC, Polyvinylchloride Low Smoke and Fume extruded compound
Color : Black (or to be agreed)
Thickness : 1,6 mm
Overall diameter : 18,5 mm
Total weight : 600 Kg/Km

Marking :

On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.

Performance :

- Conductor resistance 26 ohm/Km (+ 5% for multipair)
- Test voltage core to core 2 Kv
- Flame retardant according to IEC60332-3-24, CEI20-22/3
- Low smoke and fume as per IEC60754-1, CEI20-37
- HCL emission \leq 22%
- Minimum bending radius 12 V. D.
- Hydrocarbon resistant

- Inductance \leq 0,90 mH/Km
- Capacitance \leq 0,250 microF/Km

Weight and diameter are theoretical + / - 10%