

**CONTROL CABLE  
Cu, XLPE insulated, LSZH bedding, SWA, LSZH outer sheath  
IEC60332.3, IEC61034, IEC60754**

---

<b>Type</b>	<b>F-Cu/XLPE/LSZH/SWA/LSZH 0,6/1Kv FE4OM1FM1 0,6/1Kv</b>	<b>3X 2,5sqmm</b>
<b>Conductor :</b>	Flexible red copper conductor according to IEC60228 cl.5 size Diam. 2 mm	2,5sqmm ( 48x0,25 )
<b>Insulation :</b>	Cross-linked XLPE extruded compound Thickness : 0,7 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
<b>Laying up :</b>	Twisted to core, color Brown - Black - Grey ( or to be agreed )	

**Overall screen**

<b>Bedding :</b>	M1, Low Smoke Zero Halogen emission extruded compound Thickness : 1,0 mm
<b>Armor :</b>	SWA, Galvanized steel round wires Thickness : 0,9 mm
<b>Outer sheath :</b>	M1, Low Smoke Zero Halogen emission extruded compound Color : Black ( or to be agreed ) Thickness : 1,6 mm Overall diameter : 15 mm Total weight : 360 Kg/Km

**Marking :**

On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.

<b>Performance :</b>	- Conductor resistance 7,98 ohm/Km (+ 5% for multipair )
	- Test voltage core to core 4 Kv
	- Flame retardant according to IEC60332-3-22, CEI20-22/2
	- Low smoke and halogen free as per IEC60754-2, CEI20-37/2
	- Low smoke density emission IEC61034-1/2
	- Minimum bending radius 16 V. D.
	- Hydrocarbon and UV resistant

**Weight and diameter are theoretical + / - 10%**