

CONRTOL CABLE
Cu, XLPE insulated, overall screen, PVC outer sheath
IEC60332.3-22A, IEC60332.1

Type	F-Cu/XLPE/OS/PVC 0,6/1Kv FE4OHR 0,6/1Kv	2X 2,5sqmm
Conductor :	Flexible plain copper conductor according to IEC60228 cl.5 size 2,5sqmm (48x0,25) Diam. 2 mm	
Insulation :	Cross-linked XLPE extruded compound Thickness : 0,7 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
Laying up :	Twisted to core, color Blue - Brown (or to be agreed)	
Overall screen	Applied over total assembly will be wrapped with polyester tape and shielded with Aluminum/Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 size 0,5sqmm.	
Outer sheath :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Black (or to be agreed) Thickness : 1,8 mm Overall diameter : 11 mm Total weight : 180 Kg/Km	
Marking :	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
Performance :	- Conductor resistance 7,98 ohm/Km (+ 5% for multipair) - Test voltage core to core 4 Kv - Flame retardant according to IEC60332-3-22, CEI20-22/2 - Low smoke and fume as per IEC60754-1, CEI20-37 - HCL emission \leq 22% - Minimum bending radius 8 V. D. - Hydrocarbon resistant	

Weight and diameter are theoretical + / - 10%