

INSTRUMENTATION CABLE
Cu, XLPE insulated, overall screen, PVC bedding, SWB, PVC outer sheath
IEC60332.3

Type	F-Cu/XLPE/OS/PVC/SWB/PVC 450/750V FE4XOHRAR 450/750V	2X 10sqmm
Conductor :	Flexible plain copper conductor according to IEC60228 cl.5 size 10sqmm (77x0,40) Diam. 4,1 mm	
Insulation :	Cross-linked XLPE extruded compound Thickness : 0,7 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
Laying up :	Twisted to pair, color Red - Black (or to be agreed)	
Overall screen	Applied over total assembly will be wrapped with polyester tape and shielded with Aluminum/Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 size 0,5sqmm.	
Bedding :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Thickness : 1,0 mm	
Armour :	SWB, Galvanized steel braid wires Thickness : 0,3 mm	
Outer sheath :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Red (or to be agreed) Thickness : 2,0 mm Overall diameter : 20 mm Total weight : 710 Kg/Km	
Marking :	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
Performance :	- Conductor resistance 1,91 ohm/Km (+ 5% for multipair) - Test voltage core to core 3 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and fume as per IEC60754-1, CEI20-37 - HCL emission <= 22% - Minimum bending radius 12 V. D. - Hydrocarbon UV resistant - Inductance <= 0,90 mH/Km - Capacitance <= 0,250 microF/Km	

Weight and diameter are theoretical + / - 10%