

**INSTRUMENTATION CABLE**  
**Cu, XLPE insulated, overall screen, PVC bedding, SWB, PVC outer sheath**  
**IEC60332.3**

---

<b>Type</b>	<b>F-Cu/XLPE/OS/PVC/SWB/PVC 450/750V FE4OHRAR 450/750V</b>	<b>2X 16AWG</b>
<b>Conductor :</b>	Flexible plain copper conductor according to IEC60228 cl.5 size 16AWG ( 28x0,25 ) Diam. 1,55 mm	
<b>Insulation :</b>	Cross-linked XLPE extruded compound Thickness : 0,7 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
<b>Laying up :</b>	Twisted to pair, color White - Black ( or to be agreed )	
<b>Overall screen</b>	Applied over total assembly will be wrapped with polyester tape and shielded with Aluminum/Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 size 0,5sqmm.	
<b>Bedding :</b>	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Thickness : 1,0 mm Under arm. diameter 8,6 mm	
<b>Armour :</b>	SWB, Galvanized steel braid wires Thickness : 0,3 mm	
<b>Outer sheath :</b>	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Blue ( or to be agreed ) Thickness : 1,4 mm Overall diameter : 12,6 mm Total weight : 260 Kg/Km	
<b>Marking :</b>	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
<b>Performance :</b>	- Conductor resistance 13,3 ohm/Km ( + 5% for multipair ) - Test voltage core to core 3 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and fume as per IEC60754-1, CEI20-37 - HCL emission <= 22% - Minimum bending radius 12 V. D. - Hydrocarbon UV resistant  - Inductance <= 0,90 mH/Km - Capacitance <= 0,250 microF/Km	

**Weight and diameter are theoretical + / - 10%**