

**INSTRUMENTATION CABLE  
Cu, XLPE insulated, PVC bedding, SWB, PVC outer sheath  
IEC60332.3, IEC60502**

---

<b>Type</b>	<b>F-Cu/XLPE/PVC/SWB/PVC 0,6/1Kv FE4ORAR 0,6/1Kv</b>	<b>5G 2,5sqmm</b>
<b>Conductor :</b>	Flexible plain copper conductor according to IEC60228 cl.5 size 2,5sqmm ( 48x0,25 ) Diam. 2 mm	
<b>Insulation :</b>	Cross-linked XLPE extruded compound Thickness : 0,7 mm	- Temperature range -50 + 90°C - Temperature laying -5 + 90°C
<b>Laying up :</b>	Twisted to core, color Blue - Brown - Black - Grey - Y/G ( or to be agreed )	

**Bedding :** PVC, Polyvinylchloride Low Smoke and Fume extruded compound  
Thickness : 1,0 mm

**Armour :** SWB, Galvanized steel braid wires  
Thickness : 0,3 mm

**Outer sheath :** PVC, Polyvinylchloride Low Smoke and Fume extruded compound  
Color : Black ( or to be agreed )  
Thickness : 1,8 mm  
Overall diameter : 17,5 mm  
Total weight : 530 Kg/Km

**Marking :**

On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.

**Performance :**

- Conductor resistance 7,98 ohm/Km ( + 5% for multipair )
- Test voltage core to core 3,5 Kv
- Flame retardant according to IEC60332-3-24, CEI20-22/3
- Low smoke and fume as per IEC60754-1, CEI20-37
- HCL emission  $\leq$  22%
- Minimum bending radius 14 V. D.
- Hydrocarbon and UV resistant
  
- Inductance  $\leq$  0,90 mH/Km
- Capacitance  $\leq$  0,075 microF/Km

**Weight and diameter are theoretical + / - 10%**