

**INSTRUMENTATION CABLE**  
**Cu, XLPE insulated, Cu individual and overall screen, PVC bedding, STA, PVC outer sheath**  
**IEC60332.3, IEC60584**

---

<b>Type</b>	<b>F-Kx/XLPE/ISH1/OSH1/PVC/STA/PVC 450/750V 6X2X 1sqmm</b> <b>Kx FE4XH1OH1RNR 450/750V</b>
<b>Conductor :</b>	Flexible conductor according to IEC60584 NiCr + / Ni -, size 1sqmm (12x0,32) Diam. 1,3 mm
<b>Insulation :</b>	Cross-linked XLPE extruded compound - Temperature range -20 + 90°C Thickness : 0,6 mm - Temperature laying -5 + 90°C
<b>Laying up :</b>	Twisted to pair, color Green + , White - numbered ( or to be agreed )
<b>Pair/Triad screen</b>	Applied over the single pair/triad will be wrapped with polyester tape and shielded with Copper / Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 size 0,5sqmm, over the screen will be placed a further Mylar tape.
<b>Overall screen</b>	Applied over total assembly will be wrapped with polyester tape and shielded with Copper/Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 size 0,5sqmm.
<b>Bedding :</b>	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Thickness : 1,0 mm
<b>Armour :</b>	STA, Double galvanized steel tape Thickness : 0,25 mm
<b>Outer sheath :</b>	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Green ( or to be agreed ) Thickness : 1,6 mm Overall diameter : 23 mm Total weight : 820 Kg/Km
<b>Marking :</b>	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.
<b>Performance :</b>	- Conductor resistance 19,5 ohm/Km (+ 5% for multipair ) - Test voltage core to core 3 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and fume as per IEC60754-1, CEI20-37 - HCL emission <= 22% - Minimum bending radius 14 V. D. - Hydrocarbon and UV resistant

**Weight and diameter are theoretical + / - 10%**