

**FIRE RESISTANT INSTRUMENTATION CABLE**  
**CuMGT, EPR insulated, individual and overall screen, LSZH bedding, SWB, LSZH outer sheath**  
**IEC60332.3, IEC60754, IEC61034, IEC60331-23**

---

<b>Type</b>	<b>Ft-CuMGT/EPR/IS/OS/LSZH/SWB/LSZH 0,6/1Kv</b>	<b>3X2X 1,5sqmm</b>
	<b>FTG10XHOHM1AM1 0,6/1Kv</b>	
<b>Conductor :</b>	Flexible tinned copper conductor according to IEC60228 cl.5 siz 1,5sqmm ( 28x0,25 ) Diam. 1,55 mm	
<b>Insulation :</b>	Mica tape, Cross-linked XLPE extruded compound - Temperature range -20 + 90°C Thickness : 0,7 mm - Temperature laying -5 + 90°C	
<b>Laying up :</b>	Twisted to pair, Blue - Black numbered ( or to be agreed )	
<b>Pair screen</b>	Each pair will be shielded with aluminium/mylar tape, with tinned copper drain wire 7x0,30 placed between the aluminium/myler tape and further myler tape.	
<b>Overall screen</b>	Over the multipair will be shielded with aluminium/mylar tape, with tinned copper drain wire 7x0,30 placed between the aluminium/myler tape and further myler tape.	
<b>Bedding :</b>	M1, Low Smoke Zero Halogen emission extruded compound Thickness : 1,0 mm	
<b>Armour :</b>	SWB, Galvanized steel braid wires Thickness : 0,3 mm	
<b>Outer sheath :</b>	M1, Low Smoke Zero Halogen emission extruded compound Colour : Red ( or to be agreed ) Thickness : 1,8 mm Overall diameter : 22 mm Total weight : 710 Kg/Km	
<b>Marking :</b>	On the outhter sheath " manufacturer's name year & description cable " with ink-jet printer.	
<b>Performance :</b>	- Conductor resistance 13,3 ohm/Km (+ 5% for multipair ) - Test voltage core to core 3,5 Kv - Flame retardant according to IEC60332.3-22, CEI20-22/2 - Low smoke and halogen free as per IEC60754-2, CEI20-37/2 - Fire resistant IEC60331-23 - Minimum bending radius 16 v.d.	