

**FIRE RESISTANT INSTRUMENTATION CABLE**  
**Tinned Cu, MGT, XLPE insulated, overall screen, LSZH bedding, GSWA, LSZH outer sheath**  
**IEC60332.3, IEC60754, IEC61034, IEC60331-21**

---

<b>Type</b>	<b>Ft-Cu/MGT/XLPE/OS/LSZH/GSWA/LSZH 0,6/1Kv</b>	<b>2X 2,5sqmm</b>
	<b>FtTG10OHM1FM1 0,6/1Kv</b>	
<b>Conductor :</b>	Flexible tinned copper conductor according to IEC60228 cl.5 siz 2,5sqmm ( 48x0,25 ) Diam. 2 mm	
<b>Insulation :</b>	Mica tape, Cross-linked XLPE extruded compound - Temperature range -20 + 90°C Thickness : 0,7 mm - Temperature laying -5 + 90°C	
<b>Laying up :</b>	Twisted to pair, White - Black ( or to be agreed )	
<b>Pair screen</b>		
<b>Overall screen</b>	Over the multipair will be shielded with aluminium/mylar tape, with tinned copper drain wire 7x0,30 placed between the aluminium/myler tape and further myler tape.	
<b>Bedding :</b>	M1, Low Smoke Zero Halogen emission extruded compound Thickness : 1,0 mm	
<b>Armour :</b>	SWA, Galvanized steel round wires Thickness : 0,9 mm	
<b>Outer sheath :</b>	M1, Low Smoke Zero Halogen emission extruded compound Colour : Red ( or to be agreed ) Thickness : 1,8 mm Overall diameter : 15,8 mm Total weight : 400 Kg/Km	
<b>Marking :</b>	On the outhter sheath " manufacturer's name year & description cable " with ink-jet printer.	
<b>Performance :</b>	- Conductor resistance 7,98 ohm/Km (+ 5% for multipair ) - Test voltage core to core 3,5 Kv - Flame retardant according to IEC60332.3-22, CEI20-22/2 - Low smoke and halogen free as per IEC60754-2, CEI20-37/2 - Fire resistant IEC60331-21 - Minimum bending radius 16 v.d.	