

**INSTRUMENTATION CABLE
Cu, PVC insulated, PVC bedding, SWA, PVC outer sheath
IEC60332.3, IEC60502**

Type	Ft-Cu/PVC/PVC/SWA/PVC 0,6/1Kv FR2ORFR 0,6/1Kv	3G 4sqmm
Conductor :	Flexible tinned copper conductor acc. to IEC60228 cl.5 Diam. 2,5 mm	size 4sqmm (56x0,30)
Insulation :	PVC extruded compound Thickness : 1,0 mm	- Temperature range -15 + 70°C - Temperature laying -5 + 70°C
Laying up :	Twisted to core, color Yellow - Blue - Y/G (or to be agreed)	

Bedding : PVC, Polyvinylchloride Low Smoke and Fume extruded compound
Thickness : 1,0 mm

Armour : SWA, Galvanized steel round wires
Thickness : 0,9 mm

Outer sheath : PVC, Polyvinylchloride Low Smoke and Fume extruded compound
Color : Black (or to be agreed)
Thickness : 1,8 mm
Overall diameter : 17,6 mm
Total weight : 510 Kg/Km

Marking :

On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.

Performance :

- Conductor resistance 5,09 ohm/Km (+ 5% for multipair)
- Test voltage core to core 3,5 Kv
- Flame retardant according to IEC60332-3-24, CEI20-22/3
- Low smoke and fume as per IEC60754-1, CEI20-37
- HCL emission \leq 22%
- Minimum bending radius 12 V. D.
- Hydrocarbon and UV resistant

- Inductance \leq 0,90 mH/Km
- Capacitance \leq 0,250 microF/Km

Weight and diameter are theoretical + / - 10%