

**FIRE RESISTANT POWER CABLE  
CuMGT, FR-XLPE insulated, LSZH bedding, SWA, LSZH outer sheath  
IEC60332.3, IEC60754, IEC61034, IEC60331-21**

---

<b>Type</b>	<b>R-CuMGT/XLPE/LSZH/SWA/LSZH 0,6/1Kv RTE40M1FM1 0,6/1Kv</b>	<b>3X 1,5sqmm</b>
<b>Conductor :</b>	Strandrd plain copper conductor according to IEC60228 cl.2 siz 1,5sqmm ( 7x0,53 ) Diam. 1,55 mm	
<b>Insulation :</b>	Mica tape, Cross-linked FR-XLPE extruded compound - Temperature range -20 + 90°C Thickness : 0,7 mm - Temperature laying -5 + 90°C	
<b>Laying up :</b>	Twisted to core, Red - Blue - Black ( or to be agreed )	
<b>Pair screen</b>		
<b>Overall screen</b>		
<b>Bedding :</b>	M1, Low Smoke Zero Halogen emission extruded compound Thickness : 1,0 mm	
<b>Armour :</b>	SWA, Galvanized steel round wires Thickness : 0,9 mm	
<b>Outer sheath :</b>	M1, Low Smoke Zero Halogen emission extruded compound Colour : Black ( or to be agreed ) Thickness : 1,8 mm Overall diameter : 14,4 mm Total weight : 340 Kg/Km	
<b>Marking :</b>	On the outhter sheath " manufacturer's name year & description cable " with ink-jet printer.	
<b>Performance :</b>	<ul style="list-style-type: none"><li>- Conductor resistance 12,1 ohm/Km (+ 5% for multipair )</li><li>- Test voltage core to core 3,5 Kv</li><li>- Flame retardant according to IEC60332.3-22, CEI20-22/2</li><li>- Low smoke and halogen free as per IEC60754-2, CEI20-37/2</li><li>- Fire resistant IEC60331-21</li><li>- Minimum bending radius 16 v.d.</li><li>- Hydrocarbon and UV resistant</li></ul>	