

**INSTRUMENTATION CABLE**  
**CuMGT, FR-HEPR insulated, individual and overall screen, LSZH outer sheath**  
**IEC60332.3-24, IEC60754, IEC61034, IEC60331-21**

---

<b>Type</b>	<b>F-Cu/MGT/FR-HEPR/IS/OS/LSZH 300/500V FTG18XHOHM16 300/500V</b>	<b>12X2X 1,5sqmm</b>
<b>Conductor :</b>	Flexible plain copper conductor according to IEC60228 cl.5 size 1,5sqmm ( 28x0,25 ) Diam. 1,55 mm	
<b>Insulation :</b>	Mica tape, Cross-linked G18 extruded compound Thickness : 0,6 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
<b>Laying up :</b>	Twisted to pair, color Blue - Black numbered ( or to be agreed )	
<b>Pair/Triad screen</b>	Applied over the single pair/triad will be wrapped with polyester tape and shielded with Aluminum / Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 size 0,5sqmm, over the screen will be placed a further Mylar tape.	
<b>Overall screen</b>	Applied over total assembly will be wrapped with polyester tape and shielded with Aluminum/Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 size 0,5sqmm.	
<b>Outer sheath :</b>	M16, Low Smoke Zero Halogen emission extruded compound Color : Red ( or to be agreed ) Thickness : 2,0 mm Overall diameter : 30 mm Total weight : 1180 Kg/Km	
<b>Marking :</b>	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
<b>Performance :</b>	<ul style="list-style-type: none"><li>- Conductor resistance 13,3 ohm/Km ( + 5% for multipair )</li><li>- Test voltage core to core 2 Kv</li><li>- Flame retardant according to IEC60332-3-24, CEI20-22/3</li><li>- Low smoke and halogen free as per IEC60754-2, CEI20-37/2</li><li>- Low smoke density emission IEC61034-1/2</li><li>- Minimum bending radius 15 V. D.</li><li>- Hydrocarbon and UV resistant</li> <li>- Inductance &lt;/= 0,90 mH/Km</li><li>- Capacitance &lt;/= 0,250 microF/Km</li><li>- Fire resistant IEC60331-21</li></ul>	

**Weight and diameter are theoretical + / - 10%**