

**THERMOCOUPLE EXTENSION CABLE  
JX, PVC insulated, overall screen, PVC outer sheath  
IEC60332.3, DIN43714**

---

<b>Type</b>	<b>JX PVC/OS/PVC 300/500V JX FR2XOHR 300/500V</b>	<b>8X2X 0,8sqmm</b>
<b>Conductor :</b>	Stranded alloy conductor according to Diam. 1,12 mm	DIN43714 0,8sqmm ( 10x0,32 )
<b>Insulation :</b>	PVC extruded compound Thickness : 0,5 mm	- Temperature range -15 + 70°C - Temperature laying -5 + 70°C
<b>Laying up :</b>	Twisted to pair : + Red / - Blue numbered	
<b>Pair screen</b>		
<b>Overall screen</b>	Over the multipair will be shielded with aluminium/mylar tape, with tinned copper drain wire 7x0,30 placed between the aluminium/myler tape and further myler tape.	
<b>Bedding :</b>	Thickness : mm	
<b>Armor :</b>	Thickness : mm	
<b>Outer sheath :</b>	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Blue Thickness : 1,6 mm Overall diameter : 17 mm Total weight : 400 Kg/Km	
<b>Marking :</b>	On the outhter sheath " manufacturer's name year & description cable " with yellow ink-jet printer.	
<b>Performance :</b>	<ul style="list-style-type: none"><li>- Type of conductor Jx + FE / - CuNi</li><li>- Test voltage core to core 2 Kv</li><li>- Flame retardant according to IEC60332-3-24, CEI20-22/3</li><li>- Low smoke and fume as per IEC60754-1, CEI20-37</li><li>- HCL emission &lt;/= 22%</li><li>- Minimum bending radius 8 V. D.</li><li>- Hydrocarbon resistant</li></ul>	