

POWER CABLE
Cu, FR-XLPE insulated, PVC bedding, SWA, PVC outer sheath
IEC60332.3-22 A, Gen to IEC60502

Type	R-Cu/FR-XLPE/PVC/SWA/PVC 0,6/1Kv RE4ORFR 0,6/1Kv	5G 4sqmm
Conductor :	Stranded plain copper conductor according to IEC60228 cl.2 size 4sqmm (7x0,85) Diam. 2,5 mm	
Insulation :	Cross-linked FR-XLPE extruded compound Thickness : 0,7 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
Laying up :	Twisted to core, color Y/G - Red - Yellow - Blue - Black (or to be agreed)	
Bedding :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Thickness : 1,0 mm	
Armour :	SWA, Galvanized steel round wires Thickness : 0,9 mm	
Outer sheath :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Black (or to be agreed) Thickness : 2,0 mm Overall diameter : 18,8 mm Total weight : 680 Kg/Km	
Marking :	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
Performance :	- Conductor resistance 4,61 ohm/Km (+ 5% for multipair) - Test voltage core to core 3,5 Kv - Flame retardant according to IEC60332-3-22, CEI20-22/2 - Low smoke and fume as per IEC60754-1, CEI20-37 - HCL emission <= 17% - Minimum bending radius 14 V. D. - Hydrocarbon and UV resistant	

Weight and diameter are theoretical + / - 10%