

INSTRUMENTATION CABLE
Cu, PE insulated, overall screen, PVC bedding, SWA, PVC outer sheath
IEC60332.1, IEC60332.3, EN50288-7

Type	R-Cu/PE/OS/PVC/SWA/PVC 300/500V REOHRFR 300/500V	2X 1,5sqmm
Conductor :	Stranded plain copper conductor according to IEC60228 cl.2 size 1,5sqmm (7x0,53) Diam. 1,55 mm	
Insulation :	Polyethylene extruded compound Thickness : 0,5 mm	- Temperature range -20 + 70°C - Temperature laying -5 + 70°C
Laying up :	Twisted to pair, color White - Black (or to be agreed)	
Overall screen	Applied over total assembly will be wrapped with polyester tape and shielded with Aluminum/Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 size 0,5sqmm.	
Bedding :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Thickness : 1,0 mm	
Armour :	SWA, Galvanized steel round wires Thickness : 0,9 mm	
Outer sheath :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Blue (or to be agreed) Thickness : 1,4 mm Overall diameter : 12,6 mm Total weight : 260 Kg/Km	
Marking :	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
Performance :	- Conductor resistance 12,1 ohm/Km (+ 5% for multipair) - Test voltage core to core 2 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and fume as per IEC60754-1, CEI20-37 - HCL emission <= 22% - Minimum bending radius 14 V. D. - Hydrocarbon and UV resistant	

Weight and diameter are theoretical +/- 10%